

Product	LuxeWall® Luxury Wall Cladding
Product Description	LuxeWall® is a modern, lightweight residential wall cladding solution developed with a concealed fixing system to fasten to timber and metal stud wall framing. The system uses architectural steel faced insulated wall cladding conceal fixed in a vertical orientation. LuxeWall® is available in standard wall thicknesses of 50mm & 75mm (Note: 90 to 200mm wall thicknesses are available via special order).
Supplier	BONDOR®
Contact Number	1300 300 099
Website	www.bondor.com.au
Product Overview	
Core	EPS-FR with CorePlus® MW (Mineral Wool)
Width (cover mm)	900 [^] , 1200 ([^] available on request)
Thickness (mm)	50, 75 (other thicknesses available on request)
Length	Up to 6.5m (check for availability)
External Material	Bluescope® COLORBOND® Steel 0.6mm G300
External Finishes	Plain, VJ [^] ([^] available on request)
Exterior Colour Options	Metallic Cosmic®, Metallic Astro®, Matt Basalt®, Matt Surfmist®
Internal Material	Bluescope® COLORBOND® Steel 0.6mm G300 with HygienePlus®
Internal Finishes	Plain
Interior Colour Options	Surfmist®
Paint System	AS/NZS 2728 & AS 1397
Accreditations	Codemark Certificate Number CM40203
Acoustic Properties	Rw 35, 40 (EPS), 40, 45 (MW) *depending on construction
Material Group Numbers	C1.10 Group 1
Bushfire Attack Level	BAL-40 (All exposed core to be covered with flashing)
Technical Properties	
Thermal - AS/NZS 4859.1	
Total R-Value (m²K/W)	50, 75mm SL Grade LuxeWall® delivers Total R-value of 1.9, 2.5 for insulation average temperature of 15°C. Contact us for other temperatures and construction methods.
Acoustics - AS 1191, AS/NZS 1276 & AS/NZS ISO 717 .1	
Rw Value (dB)	LuxeWall® has been tested in accordance with the requirements of AS 1191. The Weighted Sound Reduction Index (Rw) of the panel is calculated using AS/NZS 1276 and AS/NZS ISO 717.1 respectively with acoustic values of Rw 35 or 40 for EPS & 40 or 45 for MW. Refer to Bondor® Australia for your specific application.
Fire	
Combustibility	AS 1530.1 Non-combustible (MW)
Fire hazard properties	AS/NZS 1530.3
Ignitability Index	0
Spread of Flame Index	0
Heat Evolved Index	0
Smoke Index	2-3
Ave. Specific Extinction Area	< 250m²/kg
Material Group Numbers AS 5637.1 / AS ISO 9705	LuxeWall® EPS-FR & MW steel skinned insulated building panels conform to the requirements of the BCA Specification C1.10 as Group 1. Group 1 - Panel up to 250mm thick with steel 'wall-wall' and 'wall-ceiling' angles fixed with steel rivets or screws at 300mm centres is classified as Group 1.
Bushfire Attack Level AS 3959	LuxeWall® is suitable for use as external walls of Class 1 and 10 buildings to be constructed in designated bushfire prone areas that have a BAL-40 or less.

Structural - AS/NZS 1170, AS 1562.1, AS4040	
Span Tables	Bondor® provides the latest Ultimate Limit State Span Tables developed specifically for Australasian conditions, in accordance with AS/NZS 1170, AS 1562.1 & AS 4040. Refer to Span Tables for detail'd design guidelines and Span Tables for Non-Cyclonic Regions A & B. Refer to Span Table Notes for design guidelines relating to fixing, and deflection limits. The panel design shall be specified by the certifying engineer as determined from the Span Tables.
Support Details	The support spacing shall be specified by the structural engineer as determined from the Span Tables.
Safe Handling & Installation	
Panel Length	Up to 16m, however site, transport and wind load restrictions can limit panel length.
Storage	Panels should always be kept dry and if placed on site, stored off the ground, slightly inclined, allowing adequate drainage and ventilation of the panel pack. No other materials to be stored / stacked on top of panel pack.
Handling	In the event of manual handling, careful consideration should be given to panel weight and appropriate PPE. Consider using mechanical aides if necessary.
Safety	The contractor is to determine and use safe working methods throughout the installation and construction period, which complies with OHS requirements. A safe work method template (although NOT project specific) is available from Bondor®.
Supporting Frame	The builder is to ensure that the substrates including slabs and kerbs; and sub frames are straight, smooth and fit for purpose.
Fixing	Fixings are to meet the requirements of Bluescope TB-16 Fasteners for Roofing and Wall'ng Product Selection Guide. Fasteners must be manufactured from high grade carbon steel with a minimum class 4 anti-corrosion coating as per Australian Standards. Refer to Span Tables Notes for design guide relating to screw fixing and IPCA for cold storage compliance.
Flashing	Flashings are manufactured from 0.55mm Bluescope COLORBOND® steel and installed to AS 1562.1 or as otherwise specified in the Bondor® Cold Storage or Cladding Construction Drawings. Aluminium can be used if there is no Group Number requirement.
Sealant	Sealant to be neutral cure and meet recommendations for sealants as per Bluescope TB-9 Sealants for Exterior Finishes. Silicon, polyurethane, butyl mastic and acrylic based sealants may be appropriate if neutral cure and recommended by their manufacturer for use on COLORBOND® steel and for the application. Sealant to be placed between flashings/angles and panel and between panel joints as shown on the Bondor® Standard Construction Details.
Installation	<p>Installation as per the Bondor® Standard Construction Details.</p> <ul style="list-style-type: none"> • Panels are to be cut & trimmed to ensure a flush finish. • Panels are to be confirmed square & plumb as per project requirements. • Panels are to be cut with a suitable metal cutting circular type saw. Angle grinder is not recommended. • Penetrations for outlets, vents, flues etc. are to be flashed & sealed with appropriate materials. Refer flashing details above. • Gaps to be filled with a suitable sealant or foam filler. • Refer to Bondor® Standard Construction Details & Fixing Details above for fastener requirements. • Remove all swarf and any foreign matter immediately from all panel surfaces as per Bluescope TB-5 Swarf staining of steel profiles.
Maintenance	Refer to Bluescope TB-4 Maintenance of COLORBOND® and Zinalume® Steel and the relevant Bondor® maintenance information.
Warranties & Disclaimers	
Warranty	Bondor® offer a conditional warranty up to 15 years on LuxeWall® for use as architectural wall panels from install date for projects on an application basis, dependent on project location, design, installation, end use, environmental conditions and maintenance of the product. Please contact the Bondor® sales team with your specific project details for more information on the available conditional warranties.
Disclaimers	Under certain light conditions this product may show an undulating surface which can vary depending on exterior profile and steel gauge selection as well as the environments varying light conditions.